

# VOICE SOUNDERS & BEACONS (VADS)



C-3-8 Addressable Base VAD  
Voice Sounder (pictured with a  
Context Plus detector/base)  
Part Number CON457A/CX/W

## C-3-8 Addressable Base VAD c/w Voice Sounder CON457A/CX/W

- Superb sound intelligibility.
- Includes three selectable voice message pairs.
- Provides 'C-3-8' light distribution
- Onboard short-circuit loop isolator.
- 550 $\mu$ A quiescent and 19.5mA alarm current @24V DC (VAD lit, voice sounder on max).
- 7 selectable volume levels.
- Suitable for use with a Context Plus detector and base..
- Optional BF330CTLIDW white or BF330CTLIDR red cap available for stand-alone use.
- IP21C rated.
- Optional custom messages in different languages - call for details



Addressable Base Voice Sounder  
(pictured with a Context Plus  
detector/base)  
Part Number CON454A/CX/W

## Addressable Base Voice Sounder CON454A/CX/W

- Superb sound intelligibility.
- Includes three selectable voice message pairs.
- Onboard short-circuit loop isolator.
- 550 $\mu$ A quiescent and 10mA alarm current @24V DC (voice sounder on max).
- Group addressing facility allows multiple devices to be operated simultaneously.
- 7 selectable volume levels.
- Suitable for use with a Context Plus detector and base..
- Optional BF330CTLIDW white or BF330CTLIDR red cap available for stand-alone use.
- IP21C rated
- Optional custom messages in different languages - call for details



Hi-Output Wall VAD with Voice  
Sounder  
Part Number CON447A/CX/DR

## Deep base Hi-Output W-2.4-8.2 Wall VAD c/w Voice Sounder CON447A/CX/DR

- Superb sound intelligibility.
- Includes three selectable voice message pairs.
- Provides 'W-2.4-8.2' light distribution
- Onboard short-circuit loop isolator.
- 550 $\mu$ A quiescent and 19.5mA alarm current @24V DC (VAD lit, voice sounder on max).
- 7 selectable volume levels and up to 15 selectable tone pairs.
- IP33C rated.
- Optional custom messages in different languages - call for details



Hi-Output Wall Voice Sounder  
Part Number CON446A/CX/DR

## Deep base Hi-Output Wall Voice Sounder CON446A/CX/DR

- Superb sound intelligibility.
- Includes three selectable voice message pairs.
- Onboard short-circuit loop isolator.
- 550 $\mu$ A quiescent and 10mA alarm current @24V DC (voice sounder on max).
- 7 selectable volume levels and up to 15 selectable tone pairs.
- IP33C rated.
- Optional custom messages in different languages - call for details