



Fire Signalling

EN54-3 Compliant FirePlus Platform Sounder, Sounder and Sounder Beacons

FirePlus Sounder

FEATURES

- ◆ 32 tones plus a selectable override tone
- ◆ Shallow base IP21C and deep base IP33C, IP65 versions available
- ◆ Independently certified to IP65
- ◆ Unique twist and lock bayonet mounting system
- ◆ Fully approved to EN54-3 by LPCB
- ◆ Removable cover on deep base for surface wiring
- ◆ Features base locking system as standard



Sound Level	Low	Med	High
Typical sound Output @ 1m (Tone 1) dB(A)	82.1	97.6	102.3
Current Consumption @24Vdc mA	8.3	16.4	30.8

Voltage range (Vdc): 21.6-28 **Operating frequency (Hz):** 440-2900Hz **Temperature range:** -20(°C) to +70(°C) **Protection rating** IP21C (shallow) IP33C, IP65 (deep base) **Weight** 0.22kg (shallow base) 0.25kg (deep base)

CP550DB FirePlus DB sounder, red body deep base (IP65), LPCB approved

FirePlus Sounder/Beacon

FEATURES

- ◆ Sounder function fully approved EN54-3
- ◆ 32 tones plus a selectable override tone
- ◆ Shallow base IP21C and deep base IP33C, IP65 versions available
- ◆ Switch selectable beacon only feature
- ◆ Independently certified to IP65
- ◆ Unique twist and lock bayonet mounting system
- ◆ Removable cover on deep base for surface wiring
- ◆ Fully approved to EN54-3 by Intertek

Sound Level	Low	Med	High
Typical sound Output @ 1m (Tone 1) dB(A)	79.7	95.4	99.1
Current Consumption @24Vdc mA	10.8	19.9	34.4

Voltage range (Vdc): 21-28 **Operating frequency (Hz):** 440-2900Hz **Temperature range:** -20(°C) to +70(°C) **Protection rating** IP21C (shallow base) IP33C, IP65 (deep base) **Weight** 0.22kg (shallow base) 0.25kg (deep base)



CP750CDB FirePlus CDB sounder/beacon, red body, red lens, deep base (IP65)

FirePlus Platform Sounder

FEATURES

- ◆ 32 tones plus a selectable override tone
- ◆ Switch selectable volume control
- ◆ Modern ultra low profile for discreet mounting
- ◆ Fully approved to EN54-3 by LPCB
- ◆ Designed to accept most leading detector bases



Sound Level	High
Typical sound Output @ 1m (Tone 1) dB(A)	93.8
Current Consumption @24Vdc mA	12.0



Voltage range (Vdc): 18-30 **Operating frequency (Hz):** 440-2900Hz **Temperature range:** -20(°C) to +40(°C) **Protection rating** IP21C **Weight** 0.11kg

CP850BS FirePlus BS base sounder, white, LPCB approved

Manufactured in England

Context Plus Limited, Newby Industrial Estate, Newby Road, Hazel Grove SK7 5DA, United Kingdom

TEL: + 44 161 257 2541 , FAX: + 44 161 225 8817, Email: sales@contextplus.co.uk www.contextplus.co.uk

Context[®]
Plus