

### 1/4" FLEXIBLE HOSE AND FITTINGS



Flex hoses are used to connect the agent storage containers to the manifold in multiple cylinders arrangement. Flex hoses are constructed of high pressure hydraulic rubber in the 1/4" size and stainless steel corrugated inner core with stainless steel braided in the 1/4" size. Both ends has 7/16" - 20 UNF Flare connection.

It comes with various options of fittings of 7/16-20 UNF Flare Connection and 1/8" NPT Threads.

Part Number	Description
CP 50192-3	1/4" Flexible Hose x 12"
CP 50192	1/4" Flexible Hose x 20"
CP 50192-1	1/4" Flexible Hose x 24"
CP 50192-2	1/4" Flexible Hose x 36"



A



B



C



D

	Part Number	Description
A	CP 50194-6	1/8" NPT x 7/16-20-UNF Flare Elbow
B	CP 50194-1A	1/8" NPT & 7/16-20-UNF Flare T-Joint
C	CP 50194	1/8" NPT to 7/16-20-UNF Flare Nipple
D	CP 70191-A	7/16-20-UNF Nipple Cap

## HFC-227ea Clean Agent Fire Suppression System

Context Plus Limited, 175 Mauldeth Road, Manchester M14 6SG, England, United Kingdom

Tel: +44 161 257 2541 Fax: +44 161 225 8817 Website: [www.xportsales.com](http://www.xportsales.com) Email: [contextplus@xportsales.com](mailto:contextplus@xportsales.com)

All specifications and information indicated above are subjected to change without prior notice. Catalog # 9759/CP Ref: CP-90225-D FEB/12